

# DRINKING FOUNTAIN AND BOTTLE FILLING STATION

PRODUCT CODE

**454**

JANUARY 2018



## Special Features

- ▲ MULTI PURPOSE DRINKING WATER SUPPLY
- ▲ HYGIENIC VANDAL RESISTANT DESIGN
- ▲ SMOOTH RADIUS FRONT CORNERS
- ▲ CONCEALED PIPEWORK
- ▲ JUNIOR HEIGHT MODEL
- ▲ WORKS WITH ALL COMMON 0.5, 0.75 and 1.0 L BOTTLES
- ▲ INDOOR AND OUTDOOR\* USE

## Description

The floor mounted junior height drinking fountain and bottle filling station is a multi-purpose unit providing a drinking water fountain with a convenient recessed bottle filling station below, the opening sized to take all common 0.5, 0.75 and 1.0 litre bottles.

The unit is hygienic, robust and is suitable for both indoor and, when proper precautions\* are observed, outdoor use. The shielded self-closing bubbler valve is positioned for ease of use and the bottle filler is activated by a simple push button tap. The whole unit features smooth and rounded front edges eliminating sharp corners which can cause injury. The drinking fountain and bottle filling station has an integral full height shroud to conceal the supply and waste pipework. The unit is supplied with flexible waste pipes terminating in one connection. Both the bubbler and tap are WRAS approved.

## Construction

The drinking fountain and bottle filling station is manufactured in one piece without joints or crevices from grade 304 stainless steel with all exposed surfaces polished to a matt finish. Drinking fountain is supplied with a flush grated waste fitting and a chrome plated shielded bubbler complete with a self-closing push button valve. Bottle filling station (recessed) is supplied with a flush grated waste and a chrome plated push button self-closing tap. The unit is supplied with a lockable side access panel for access to the pipework.

## \*Outdoor Installations

When installed outdoors it is necessary to isolate the water supply, drain completely all pipes and valves using pressurised air, if necessary, prior to temperatures falling to 0°C. Alternatively it is recommended to dismantle the fountain and store it in an area where temperatures will not fall to 0°C. If water freezes in the valves irreparable damage will be done to internal parts which will require replacing.

## Order Codes and Technical Specification

Please refer to the Technical Specification Sheet.



Unit 1, Elphicks Farm, Spelmonden Road, Horsmonden, Tonbridge. Kent TN12 8EL  
Phone: 01580 211648 E-mail: [info@cactuswatersystems.co.uk](mailto:info@cactuswatersystems.co.uk)

Cactus Water Systems / the manufacturer reserve the right to change the design and specification of goods without notice. Descriptions in this sheet are correct at time of going to press but are subject to alteration. Details of any changes will be available